



$\phi 23$ 2.8/8.5mm C		
FOCAL LENGTH		$f=8.5\text{mm}$
MAX. DIAMETER (RATIO)		$F=1:2.8\sim 22$
ELEMENT		14 GROUPS 17 ELEMENTS
PICTURE SIZE		$13.8\times 18.4\text{mm}$
ANGLE	VER. ANGLE	77.1°
	HOR. ANGLE	93.5°
	DIA. ANGLE	106.0°
DISTORTION (TV)		0.12% (WD=300mm)
SHOOTING RANGE AT	VER.	179mm
MINIMUM FOCUS	HOR.	239mm
DISTANCE	DIA.	298m
MINIMUM FOCUS DISTANCE		0.1m
FLANGE BACK		17.526mm in air
BACK FOCUS		12.9mm in air
FILTER SCREW SIZE		M72x075
FRONT/REAR EFFECTIVE DIA.		FRONT $\phi 45.5\text{mm}$ REAR $\phi 16.5\text{mm}$
MOUNT		C-MOUNT
EXIT PUPIL		-75.1mm
TEMPERATURE RANGE		$-10\sim +50^\circ\text{C}$
STORAGE TEMPERATURE RANGE		$-20\sim +60^\circ\text{C}$
RESOLUTION CENTER/CORNER		Center 160lp/mm Corner 80lp/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		245g

NOTE: Specifications and availability are subject to change without notice



		1/1		
		$\phi 23$ F2.8 $f=8.5\text{mm}$		
		1-24719		
2013.4.15				